

**NOTES:**

1. NEATLY CUT EXIST. EDGE OF PAVEMENT AND APPLY TACK COAT.
2. RESIDENTIAL DRIVEWAY APPROACH MATERIAL SHALL BE ASPHALT CONCRETE IF ROAD FRONTING DRIVEWAY IS PAVED, PAVING SHALL CONSIST OF 2" A.C. OVER 6" A.B. MINIMUM.
3. COMMERCIAL DRIVEWAY AND PRIVATE ROAD APPROACH MATERIAL SHALL BE ASPHALT CONCRETE IF ROAD FRONTING THE APPROACH IS PAVED. PAVING SHALL CONSIST OF 3" A.C. OVER 8" CL. 2 A.B. MINIMUM.
4. DRIVEWAY APPROACH SURFACING SHALL BE COMPARABLE TO THE SURFACING OF THE ADJACENT ROAD. AGGREGATE BASE SHALL BE ONE FOOT WIDER THAN THE PAVED WIDTH ON EACH SIDE.
5. CULVERT SHALL BE 12" DIA. MIN. R.C.P. OR HDPE PLASTIC PIPE WITH SMOOTH INTERIOR WALL CONFORMING TO CALTRANS STANDARD SPECIFICATIONS. IN NO CASE SHALL PIPE BE SMALLER THAN UP STREAM CULVERT. LENGTH OF THE CULVERT SHALL BE THAT REQUIRED TO EXTEND ONE FOOT BEYOND THE TOE OF THE DRIVEWAY FILL.
6. REGRADE DITCH ADJACENT TO PROPERTY LINE FOR ENTIRE FRONTAGE OF PROPERTY, IF REQUIRED.
7. CULVERT SHALL BE REQUIRED WHERE THERE IS A ROADSIDE DITCH, UNLESS FLOWLINE OF DITCH IS LESS THAN 3" BELOW EDGE OF PAVEMENT PROFILE. VALLEY GUTTER SHALL BE PROVIDED WHERE CULVERT IS NOT REQUIRED (SEE DETAIL ON STD. NO. A51A)
8. ALL DRIVEWAYS SHALL INTERSECT EXIST STREETS AT 80° MINIMUM, UNLESS OTHERWISE APPROVED BY THE DOT DIRECTOR.
9. SEE MENDOT STD NO. A52 FOR DRIVEWAY/ROAD CONNECTION PROFILE.
10. SEE MENDOT STD NO. A53 FOR SIGHT DISTANCE REQUIREMENTS.
11. AN ENCROACHMENT PERMIT SHALL BE OBTAINED PRIOR TO CONSTRUCTING A DRIVEWAY APPROACH ON A COUNTY ROAD.
12. CULVERT SIZE AND MATERIAL SUBJECT TO THE APPROVAL OF COUNTY



**DRIVEWAY APPROACH  
RURAL ROADS – NOTES**

MENDOT  
STD. NO.  
**A51C**

SCALE: NONE | DESIGN: HND | DRAWN: HND | FEB. 2008

PAGE: A-41

